

ShaliKote® T-32

Bituminous Cold Applied Clay Type Emulsions



STP Limited

Description

ShaliKote® T-32 is a clay type emulsion of selected grades of bitumen in water with inert fillers. Selected fibres are used as fillers to form a surface resistant to considerable shock and vibrations.

Characteristics

Colour	Brown to chocolate	Drying Time	24 hr
Consistency	Brushable / Trowelable	Specific Gravity	1.10
Theoretical Coverage per Coat, kg/m ²		Dry film thickness per coat, microns	
• On metal surface	0.8	• On metal surface	200
• On concrete surface	0.6	• On concrete surface	150

Application

It is recommended for waterproofing of roofs, verandahs, chajjas, etc. even under wet conditions.

Advantages

This coating, when set, is impermeable to water and shows a marked resistance to temperature fluctuations, industrial fumes and saline atmosphere.

Application Methodology

- Wire brush and clean the surface thoroughly to remove all dirt and loose particles. Repair the visible cracks and fill up the depression with 1:4 cement or sand mixture.
- Dilute **ShaliKote® T-32** from its pasty consistency to that of light consistency by adding water in the ratio of 1:1. Apply this diluted material on the roof surface as primer.
- When the primed surface is dry and has turned black from its original brown colour, apply **ShaliKote® T-32** and allow the emulsion to break. It will turn black from its original brownish colour
- When the emulsion has set in, spread coarse sand or crushed stone chips over the surface.

Health & Safety

- Lid of the container should be firmly fixed when not in use.
- Use goggles and hand gloves during application
- Clean hands with water after application.

Packing

Available in 20 kg and 200 kg drum.

Storage

Keep in cool and dry place in air tight container under shed away from heat.

Shelf Life

6 months in original unopened sealed conditions.



Advisory Cell
STP Limited
+91 81302 81114
Waterproofers to the Nation

STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

